

Display apparatus providing a uniform temperature distribution over the display unit

Publication number: EP0733927

Publication date: 1996-09-25

Inventor: SHIMADA TETSUYA (JP); KUREMATSU KATSUMI (JP); TAKABAYASHI HIROSHI (JP); YABU SHIGEKI (JP); UEHARA MAKOTO (JP); ITAZAWA TOSHIKI (JP); MAEDA YASUSHI (JP); TAKAHASHI MASANORI (JP); ONITSUKA YOSHIHIRO (JP); TAKAI KUMIHARU (JP); YUKI OSAMU (JP)

Applicant: CANON KK (JP)

Classification:

- International: G02F1/133; G09G3/34; G09G3/36; H05B41/295; H05B41/36; G02F1/13; G02F1/13357; G02F1/113; G09G3/34; G09G3/36; H05B41/28; H05B41/36; (IPC-1:7); G02F1/133

- European: G02F1/133T; G09G3/36B; G09G3/36C; G09G3/36C6B; G09G3/36C12P; G09G3/36C14P; H05B41/295; H05B41/36

Application number: EP19960301968 19960321

Priority number(s): JP19950090406 19950322; JP19950090407 19950322; JP19950090408 19950322

Also published as:

US6020867 (A1)
EP0733927 (A3)
EP0733927 (B1)

Cited documents:

US5255109
JP7049497
JP6230344
JP4172319
XP002019720
more >>

Abstract of EP0733927

A display apparatus includes: a display unit for displaying images, a backlight unit disposed behind the display unit for illuminating the display unit, an inverter unit for electrically controlling the backlight unit, a controller unit for controlling the inverter unit and the display unit, and a power supply unit having an exothermic heat distribution for supplying electricity to the inverter unit and the controller unit. The inverter unit and controller unit are disposed behind the backlight unit. The power supply unit is disposed on a side of the display unit, backlight unit, inverter unit and controller unit. The display unit, backlight unit, inverter unit, controller unit and power supply unit are disposed in a common housing. The inverter unit and said controller unit are arranged behind the backlight unit. An insulating member is further disposed between the power supply unit and the display unit at a position corresponding to a region of relatively large exothermic heat of the power supply unit so that the insulating member is disposed at a diagonal position with respect to the inverter unit. The display apparatus may be supported by a support structure including vertically tilting and laterally turning mechanisms.




FIG. 1

Data supplied from the *esp@cenet* database - Worldwide